



FEATURES

- 37 mm dial size.
- · Polycarbonate lens.
- · Stainless steel case.
- Phosphor bronze spiral tube.
- 1/8" NPT Bronze back connection.
- Accuracy up to ±4% Full scale.



APPLICATIONS

• Extinguisher equipment.



1. Working temperature -20°C to 60°C.

	MODELS	SPECIFICATIONS
Case	All models	Stainless steel
Lens	All models	Polycarbonate
Connection	All models	1/8" NPT Bronze
Movement	All models	Phosphor bronze
Accuracy	All models	Working pressure ±4%
Pointer	All models	Aluminum
Dial	All models	Aluminum, scale in MPa Designed according to NOM-045-SCFI.

* SPECIAL REQUEST

Please contact factory for special dial artwork and ranges.




○ ORDERING INFORMATION

SERIES	хт
SIZE	37mm
CASE	Aluminum
PRESSURE RANGES	1.2 MPa 0 to 1.2 MPa 1.7 MPa 0 to 1.7 MPa
EXAMPLE	 Select seriesXT Select pressure range and scale option1.7

☑ OUTLINE DIMENSIONS

XT1.2




- | 0.98" (25 mm)
- | 0.51" (13 mm)
- 0.43" (11 mm)
- (1/8" 27 NPT)



- 1.22" (31 mm)
- **2**₁ 1.45" (37 mm)

XT1.7



- | 0.98" (25 mm)
- 0.51" (13 mm)
- 0.43" (11 mm)
- (1/8" 27 NPT)



- 1.22" (31 mm)
- 1.45" (37 mm)